LE VERRE DE VIN+ classic

BERMAR

Technical specifications

Power supply: 24V DC
Power consumption: 30W (max)
Fusing: built in trip switch with push button reset
CE approved

Performance

21 days preservation
Resealing time: 1 – 5 seconds
Each system is pre-set to operate at altitudes between 0 – 500m; for locations above this level please refer to the manufacturer or your local dealer

powered by
ePreserve technoloy

What's included with each system

20x still wine eStoppers (excl. Champagne only models)
6x sparkling wine stoppers (excl. still wine only models)
A pre-set CO2 regulator (excl. still wine only models)
5m length of CO2 hose (excl. still wine only models)
Power supply configured to your region, complete with 1.5m cable
Mounting kit
12 month warranty

Sourcing CO2: Outside the UK the only item that needs sourcing locally is a food-grade CO2 supply to support sparkling wine preservation. We will be happy to recommend preferred suppliers in your market, please contact us directly.

		Wine Preservation		Height		Width		Depth	
Product	**Model No.**	**Still**	**Sparkling**	**mm**	**inch**	**mm**	**inch**	**mm**	**inch**
Classic	**BC02**	**Yes**	**Yes**	550	21.6	135	5.3	130	5.1
Classic - Still wine only	**BC02S**	**Yes**	**No**	550	21.6	135	5.3	130	5.1
Classic - Sparkling wine only	**BC02C**	**No**	**Yes**	550	21.6	135	5.3	130	5.1

		Wine Preservation		Height		Width		Depth	
Product	**Model No.**	**Still**	**Sparkling**	**mm**	**inch**	**mm**	**inch**	**mm**	**inch**
Classic | Steel Edition	**BC02SE**	**Yes**	**Yes**	550	21.6	135	5.3	130	5.1
Classic | Steel Edition - Still wine only	**BC02SES**	**Yes**	**No**	550	21.6	135	5.3	130	5.1
Classic | Steel Edition - Sparkling wine only	**BC02SEC**	**No**	**Yes**	550	21.6	135	5.3	130	5.1

+44 (0) 1473 612 062 | **sales@bermar.co.uk**